



SWG Style OR & ORIR to Suit DIN Flanges

Nominal Bore	Inner Ring ID (mm)	Sealing Element ID (mm)	Sealing Element OD		Outer Ring OD								
			PN10 - PN40 (mm)	PN64 - PN250 (mm)	PN10 (mm)	PN16 (mm)	PN25 (mm)	PN40 (mm)	PN64 (mm)	PN100 (mm)	PN160 (mm)	PN250 (mm)	
DN10	18	24	36	36	46	46	46	46	46	56	56	56	67
DN15	24	30	42	42	51	51	51	51	51	61	61	61	72
DN20	27	33	47	47	61	61	61	61	61	72	72	n/a	n/a
DN25	34	40	54	54	71	71	71	71	71	82	82	82	83
DN32	44	50	66	66	82	82	82	82	82	87	87	n/a	n/a
DN40	51	57	73	73	92	92	92	92	92	103	103	103	109
DN50	59	69	87	87	107	107	107	107	107	113	119	119	124
DN65	73	83	103	105	127	127	127	127	127	138	144	144	154
DN80	87	97	117	121	142	142	142	142	142	148	154	154	170
DN100	114	124	144	148	162	162	168	168	168	174	180	180	202
DN125	140	150	172	176	192	192	194	194	194	210	217	217	242
DN150	168	178	200	204	217	217	224	224	224	247	257	257	284
DN175	189	199	225	231	247	247	254	254	254	277	287	287	316
DN200	220	230	256	262	272	272	284	284	284	309	324	324	358
DN250	269	279	307	315	327	327	340	340	340	364	391	388	442
DN300	319	329	357	365	377	383	400	400	400	424	458	458	538
DN350	365	375	405	413	437	443	457	457	457	474	486	512	n/a
DN400	416	426	458	466	488	495	514	514	514	546	543	572	n/a
DN500	520	530	566	574	593	617	624	624	624	628	657	704	n/a
DN600	615	630	666	674	695	734	731	747	747	764	813	n/a	n/a
DN700	715	730	770	778	810	804	833	852	852	879	n/a	n/a	n/a
DN800	815	830	874	882	917	911	942	974	974	988	n/a	n/a	n/a
DN900	915	930	974	982	1017	1011	1042	1084	1084	1108	n/a	n/a	n/a
DN1000	1015	1030	1078	1086	1124	1128	1154	1194	1194	1220	n/a	n/a	n/a

Notes

Alba Gaskets Recommends that Inner Rings should be Used on Pressure Class PN100 & Above.